

# UMIB48QNR3



## Colour range

### Body



Blue  
grey - BG



Antique  
white - AW



White - WH



Blue - MB



Stainless  
steel - SS



Matt  
graphite - MG



Glossy black  
glass - BK



Burgundy  
red - BU



Emerald  
green - EG



RAL Classic - RA  
optional

## Finishes

### Knobs, handles, frames



Brass - G



Copper - P




Chrome - C



Burnished - B

Configuration

Induction



-M-	Induction zone Bridge	-H-	Induction zone Ø 5" ¼	-N-	Induction zone Ø 6" ¼	-I-	Induction zone Ø 7" ⅞
-M-	8" ¼x7" ½		1.9 / 1.45 kW		2.2 / 1.45 kW		3.1 / 2.4 kW
	+ 8" ¼x7" ½						
	3.9 / 3.1 kW						
-M-	Induction zone						
	8" ¼x7" ½						
	3.1 / 2.2 kW						

Ovens

Primary oven: UOV 80 E3 TFT S

Secondary oven: UOV 30 E3 TFT

General features

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>• Operating temperature 85-575°F</li> <li>• Programmer electronic touch TFT</li> <li>• Electronic temperature control</li> <li>• Cooking probe</li> <li>• Lighting Double internal light</li> <li>• Automatic light switch-on when door opens</li> <li>• Full glass oven door</li> <li>• Soft-closing door</li> <li>• Door glass Triple glass cold door</li> <li>• High density insulation</li> <li>• Ventilation cooling tangential</li> <li>• Child safety</li> </ul> | <ul style="list-style-type: none"> <li>• Operating temperature 85-485°F</li> <li>• Programmer electronic touch TFT</li> <li>• Electronic temperature control</li> <li>• Lighting Internal light</li> <li>• Automatic light switch-on when door opens</li> <li>• Full glass oven door</li> <li>• Soft-closing door</li> <li>• Door glass Triple glass cold door</li> <li>• High density insulation</li> <li>• Ventilation cooling tangential</li> <li>• Child safety</li> </ul> |
|--|--|

Cavity features

- |  |   |
|--|---|
| <ul style="list-style-type: none"> <li>• Muffle with easy clean enamel</li> <li>• Internal dimensions 26 3/8"x14 3/8"x16 1/8"</li> <li>• Capacity 3,5</li> <li>• Steam discharge controlled with dry or moist cooking option</li> <li>• Folding grill heating element</li> <li>• Rotisserie spit diagonal</li> <li>• Thermostat with electronic probe</li> </ul> | <ul style="list-style-type: none"> <li>• Muffle with easy clean enamel</li> <li>• Internal dimensions 10 7/8"x14" x17 5/16"</li> <li>• Capacity 1,52</li> <li>• Steam discharge</li> <li>• Rotisserie spit</li> <li>• Thermostat with electronic probe</li> </ul> |
|--|---|

Consumptions

<ul style="list-style-type: none"> <li>• Maximum input 3,7 kW</li> <li>• Top electrical heating element 1300 W</li> <li>• Bottom electrical heating element 1470 W</li> <li>• Electric grill 2340 W</li> <li>• Circular heating element 2290 W</li> </ul>	<ul style="list-style-type: none"> <li>• Maximum input 2,5 kW</li> <li>• Top electrical heating element 870 W</li> <li>• Bottom electrical heating element 870 W</li> <li>• Electric grill 1630 W</li> </ul>
---	--

Functions

Pizza function	Defrosting	Quick start	Grill cooking with closed door	Cooking from above	Cooking from below
Multiple fan cooking	Multiple moist fan cooking	Intensive cooking	Static normal cooking	ECO cooking	
Moist intensive cooking	Fan grill cooking	Grill cooking with closed door			
Cooking from above	Moist cooking from above	Cooking from below			
Moist cooking from below	Static normal cooking	Moist static normal cooking			
ECO cooking					

Technical drawing & dimensions

