

UPD40N



Colour range

Body



Blue grey - BG



Antique white - AW



White - WH



Blue - MB



Stainless steel - SS



Graphite matt - MG



Glossy black - BK



Burgundy red - BU



Emerald green - EG



RAL
Optional RAL - RA
+ \$ 2800.00

Finishes

Knobs, handles, frames (optional)



Brass - G



Copper - P



Chrome - C



Burnished - B

Optional solid door version

optional + \$ 700.00

Order code: add letter "Q" before the "N" letter

Noblesse frames

optional → p. 138

Available ovens

Electric oven

Primary oven:
UOV 60 M


Maximum input:
3.5 kW

Secondary oven:
UOV 40 E


Maximum input:
2.8 kW

Configurations

6 burners with fry top*



Induction



Electric oven

UPD40FNMP

Brass/Copper/Chrome/Burnished
\$ 7.690.00

UPDI406NMP

Brass/Copper/Chrome/Burnished
\$ 7.990.00

Fuel requirements

Natural gas / Liquid propane
Voltage: 240 Volts
Amps: 26

All electric
Voltage: 240 Volts
Amps: 74

**Insufficient amperage may lower heating performance when multiple functions are being used at the same time*

Consumption

Bridge induction zone
Ø 7" 1/4 + Ø 7" 1/4
1.85 / 2.5 kW + 1.85 kW

Induction zone
Ø 5" 3/4
1.4 / 1.8 kW

Induction zone
Ø 7" 1/4
1.85 / 2.5 kW

Induction zone
Ø 8" 11/16
2.3 / 3.2 kW

Double ring Dual burner
25000 btu/h / 900 btu/h

Griddle
10500 btu/h / 2000 btu/h + 7000 btu/h / 1400 btu/h

Big burner
10500 btu/h / 2000 btu/h

Small burner
7000 btu/h / 1400 btu/h

Complements & accessories

Hood

UAG40

\$ 2.190.00

Hood

UANB40

Brass/Copper/Chrome/Burnished
\$ 5.559.00

Ladle holder panel

AM4-100

\$ 313.00

Technical drawing & dimensions

