

# UP48W



Colour range

Body



Blue  
grey – BG



White – WH



Stainless  
steel – SS



Graphite  
matt – MG



Glossy  
black – BK

RAL

Optional RAL – RA  
+ \$ 2800.00

Finishes

Knobs, handles



Satin

Optional solid door version

optional + \$ 700.00

Order code: change letter “W” with “Q”

Available ovens

Electric oven

Primary oven:  
UOV 80 M


Maximum input:  
3.7 kW

Secondary oven:  
UOV 30 E


Maximum input:  
2.5 kW

Configurations


5 burners with fry top\* and coup de feu



8 burners with fry top\*



Induction



Electric oven

UP48FSWMP

Brushed

\$ 10.990.00

UP48FWMP

Brushed

\$ 9.990.00

UPI486WMP

Brushed

\$ 10.990.00

Fuel requirements

Natural gas / Liquid propane  
Voltage: 240 Volts  
Amps: 25.8

Natural gas / Liquid propane  
Voltage: 240 Volts  
Amps: 25.8

All electric  
Voltage: 240 Volts  
Amps: 73.8

*\*Insufficient amperage may lower heating performance when multiple functions are being used at the same time*

Consumption

<p>Bridge induction zone Ø 7" 1/4 + Ø 7" 1/4 1.85 / 2.5 kW + 1.85 kW</p>	<p>Induction zone Ø 5" 3/4 1.4 / 1.8 kW</p>	<p>Induction zone Ø 7" 1/4 1.85 / 2.5 kW</p>	<p>Induction zone Ø 8" 11/16 2.3 / 3.2 kW</p>	<p>Coupe de Feu 5500 btu/h</p>	<p>Double ring Dual burner 25000 btu/h / 900 btu/h</p>
<p>Griddle 10500 btu/h / 2000 btu/h + 7000 btu/h / 1400 btu/h</p>	<p>Oval burner 10500 btu/h / 3100 btu/h</p>	<p>Big burner 10500 btu/h / 2000 btu/h</p>	<p>Small burner 7000 btu/h / 1400 btu/h</p>		

Complements & accessories

Hood

UAGQ48

\$ 2.258.00

Ladle holder panel

AM4-120

\$ 349.00

Technical drawing & dimensions

